

On non-full-rank perfect codes over finite fields

Alexander M. Romanov*

Abstract

The paper deals with the perfect 1-error correcting codes over a finite field with q elements (briefly q -ary 1-perfect codes). We show that the orthogonal code to the q -ary non-full-rank 1-perfect code of length $n = (q^m - 1)/(q - 1)$ is a q -ary constant-weight code with Hamming weight equals to q^{m-1} where m is any natural number not less than two. We derive necessary and sufficient conditions for q -ary 1-perfect codes of non-full rank. We suggest a generalization of the concatenation construction to the q -ary case and construct the ternary 1-perfect codes of length 13 and rank 12.

1 Introduction

Let $\mathbb{F}_q^n$ be a vector space of dimension n over the finite field $\mathbb{F}_q$, where $q = p^r$, p is a prime number, r is a positive integer. The *Hamming distance* between two vectors, $\mathbf{x}, \mathbf{y} \in \mathbb{F}_q^n$, is the number of coordinates in which they differ, denoted by $d(\mathbf{x}, \mathbf{y})$. An arbitrary subset C of $\mathbb{F}_q^n$ is called a q -ary 1-perfect code of length n if for every vector $\mathbf{x} \in \mathbb{F}_q^n$ there exists a unique vector $\mathbf{c} \in C$ such that $d(\mathbf{x}, \mathbf{c}) \leq 1$. Non-trivial q -ary 1-perfect codes of length n exist only if $n = (q^m - 1)/(q - 1)$, where m is a natural number not less than two. Two codes $C_1, C_2 \subseteq \mathbb{F}_q^n$ are said to be *equivalent* if there exists a vector $\mathbf{v} \in \mathbb{F}_q^n$ and $n \times n$ monomial matrix M over $\mathbb{F}_q$ such that $C_2 = \{(\mathbf{v} + \mathbf{c}M) \mid \mathbf{c} \in C_1\}$. We assume that the all-zero vector $\mathbf{0}$ is in code. A code is called *linear* if it is a linear space over $\mathbb{F}_q$. A linear q -ary 1-perfect code of length n is unique up to equivalence and is called a q -ary *Hamming code*. Nonlinear q -ary 1-perfect codes exist for $q = 2$, $m \geq 4$, $q \geq 3$, $m \geq 3$, $q \geq 5$, $m \geq 2$. For $q = 4$, $m = 2$, the question of the existence of nonlinear q -ary 1-perfect codes still remains open, see [4, 7, 15, 16].

*Sobolev Institute of Mathematics, Russian Academy of Sciences, 4 Academician Koptyug avenue, 630090 Novosibirsk, Russia. Email: rom@math.nsc.ru

The *rank* of code C is the maximum number of linearly independent codewords of C . A code of length n that has rank n is said to have *full rank*; otherwise, the code is *non-full rank*. The rank of q -ary Hamming code of length n is equal to $n - m$ where $n = (q^m - 1)/(q - 1)$, $m \geq 2$.

The switching constructions of full-rank q -ary 1-perfect codes have been proposed for all $n = (q^m - 1)/(q - 1)$, where $m \geq 4$, see [1, 5, 15]. For $m = 3$ and for $q = p^r$, $r > 1$, the existence of full-rank q -ary 1-perfect codes is proved in [16]. The question of the existence of full-rank q -ary 1-perfect codes of length $n = (q^m - 1)/(q - 1)$ still remains open if $m = 3$, $q \geq 3$, q is a prime number, and if $m = 2$, $q \geq 4$, see [15, 16].

In the q -ary case, the question of the minimum and maximum possible cardinality of the intersection of two distinct q -ary 1-perfect codes of the same length is still open. In the binary case, this question was answered in [1, 2].

It is established that there exist at least q^{q^c} nonequivalent q -ary 1-perfect codes of length n , where $c = \frac{1}{q} - \epsilon$, see [3, 6, 7].

A *concatenation construction* of 1-perfect codes is a combinatorial generalization of the well-known $(\mathbf{u}|\mathbf{u}+\mathbf{v})$ construction. We give a description of the concatenation construction for the binary case.

Let m be any natural number not less than two and $n = 2^m - 1$. Next, let $C_0^1, C_1^1, \dots, C_n^1$ be a partition of the vector space $\mathbb{F}_2^n$ into binary 1-perfect codes of length n and let $C_0^2, C_1^2, \dots, C_n^2$ be a partition of the binary trivial MDS code with parameters $[n + 1, n, 2]$ into binary extended 1-perfect codes with parameters $(n + 1, 2^{n-m}, 4)$. (A trivial MDS code with parameters $[n + 1, n, 2]$ consists of all binary vectors of length $n + 1$ of even weight.) Then the given partitions $C_0^1, C_1^1, \dots, C_n^1$, $C_0^2, C_1^2, \dots, C_n^2$ and the permutation α acting on the index set $I = \{0, 1, \dots, n\}$ determine the binary 1-perfect code

$$C_\alpha = \{(\mathbf{u}|\mathbf{v}) \mid \mathbf{u} \in C_i^1, \mathbf{v} \in C_{\alpha(i)}^2\}$$

of length $2n + 1$.

In the binary case, the concatenation construction is based on partitions of two types – partitions of the space $\mathbb{F}_2^n$ into 1-perfect codes and partitions of the binary trivial MDS code into extended 1-perfect codes. For many decades, the question of the parameters of codes to which we must partition the trivial MDS codes in the q -ary case remained open. In this paper we obtain an answer to this question and generalize the concatenation construction to the q -ary case.

For $m \geq 4$, q -ary 1-perfect codes of length $n = (q^m - 1)/(q - 1)$ and rank $n - m + s$ exist for all $s \in \{0, 1, \dots, m\}$, see [1, 5, 15]. For $m = 3$ and for $q = p^r$, $r > 1$, the existence of q -ary 1-perfect codes of length $n = (q^3 - 1)/(q - 1)$ and rank $n - 3 + s$, $s \in \{1, 2, 3\}$ is proved in [16]. For $m = 3$, $q \geq 3$, Lindström–Schönheim codes are codes of length $n = (q^3 - 1)/(q - 1)$ and rank $n - 2$, see [6, 7]. For $m = 3$, $q \geq 3$, and for q , which is a prime number, the question of the existence of q -ary 1-perfect codes of length $n = (q^3 - 1)/(q - 1)$ and rank $n - s$, $s \in \{1, 0\}$ still remains open

[15, 16]. In particular, the question of the existence of ternary 1-perfect codes of length 13 and rank 12 remained open. In this paper we have an answer to this question. Using the q -ary concatenation construction proposed in this paper, we construct the ternary 1-perfect codes of length 13 and rank 12.

In Section 2, we show that the code orthogonal to the non-full-rank q -ary 1-perfect code of length $n = (q^m - 1)/(q - 1)$ is a q -ary constant-weight code with Hamming weight equals to q^{m-1} , where m is any natural number not less than two. In Section 3, we obtain necessary and sufficient conditions for q -ary 1-perfect codes of non-full-rank. In Section 4, we suggest a generalization of the concatenation construction to the q -ary case. In Section 5, by the concatenation construction, ternary 1-perfect codes of length 13 and rank 12 are constructed.

2 Orthogonal codes

Let $\mathbf{u}, \mathbf{v} \in \mathbb{F}_q^n$. Then the *scalar product* of the vectors $\mathbf{u} = (u_1, u_2, \dots, u_n)$ and $\mathbf{v} = (v_1, v_2, \dots, v_n)$ is the mapping

$$\mathbf{u} \cdot \mathbf{v} = \sum_{i=1}^n u_i v_i.$$

Let $C \subset \mathbb{F}_q^n$. Then the code

$$C^\perp = \{\mathbf{u} \mid \mathbf{u} \in \mathbb{F}_q^n \text{ and } \mathbf{u} \cdot \mathbf{v} = 0 \text{ for all } \mathbf{v} \in C\}$$

is *orthogonal* or *dual* of code C . The dual code of Hamming code is simplex code. The simplex code has parameters $[n, m, q^{m-1}]_q$, $n = (q^m - 1)/(q - 1)$. All words of a simplex code, with the exception of the all-zero word, have the same weight equal to q^{m-1} .

Following [1] we will use the methods described in [8], page 132. We shall represent sets of vectors from the space $\mathbb{F}_q^n$ by formal polynomials in variables $z_1, z_2, \dots, z_n$. The vector $\mathbf{v} = (v_1, v_2, \dots, v_n) \in \mathbb{F}_q^n$ corresponds to monomial $\mathbf{z}^{\mathbf{v}} = z_1^{v_1} z_2^{v_2} \dots z_n^{v_n}$. The set of all monomials in the variables $z_1, z_2, \dots, z_n$ forms a multiplicative group G whose multiplication corresponds to the addition in $\mathbb{F}_q^n$. Next, we define the group algebra QG of the group G over the field of rational numbers Q , which consists of all formal sums

$$\sum_{\mathbf{v} \in \mathbb{F}_q^n} a_{\mathbf{v}} \mathbf{z}^{\mathbf{v}}, \quad a_{\mathbf{v}} \in Q, \quad \mathbf{z}^{\mathbf{v}} \in G.$$

For each $\mathbf{u} \in \mathbb{F}_q^n$, we define the character of the group G . Let $\chi_{\mathbf{u}}(\mathbf{z}^{\mathbf{v}}) = \zeta^{\mathbf{u} \cdot \mathbf{v}}$, where ζ is a primitive q th root of unity. The character $\chi_{\mathbf{u}}$ is extended on QG by linearity. Then

$$\chi_{\mathbf{u}}(C) = \chi_{\mathbf{u}} \left(\sum_{\mathbf{v} \in C} \mathbf{z}^{\mathbf{v}} \right) = \sum_{\mathbf{v} \in C} \chi_{\mathbf{u}}(\mathbf{z}^{\mathbf{v}}) = \sum_{\mathbf{v} \in C} \zeta^{\mathbf{u} \cdot \mathbf{v}}.$$

It is known that if the code C is linear, then

$$\chi_{\mathbf{u}}(C) = \begin{cases} |C| & \text{if } \mathbf{u} \in C^\perp, \\ 0 & \text{if } \mathbf{u} \notin C^\perp. \end{cases}$$

Theorem 1. *Let C be a q -ary 1-perfect code of length $n = (q^m - 1)/(q - 1)$ and rank k . Let $\{B_0, B_1, \dots, B_n\}$ be the weight distribution of the code $C^\perp$. Then*

$$B_i = \begin{cases} 1 & \text{if } i = 0, \\ 0 & \text{if } 1 \leq i \leq q^{m-1} - 1, \\ q^{n-k} - 1 & \text{if } i = q^{m-1}, \\ 0 & \text{if } q^{m-1} + 1 \leq i \leq n. \end{cases}$$

Proof. Let $V \subset \mathbb{F}_q^n$ be a Hamming sphere of radius 1. Since the code C is q -ary 1-perfect, then $\mathbb{F}_q^n = C + V$ and, consequently, $\chi_{\mathbf{u}}(\mathbb{F}_q^n) = \chi_{\mathbf{u}}(C)\chi_{\mathbf{u}}(V) = 0$. Thus $\chi_{\mathbf{u}}(C) = 0$ if $\chi_{\mathbf{u}}(V) \neq 0$. Since $\sum_{i=0}^{q-1} \zeta^i = 0$ $\zeta^0 = 1$, then $\chi_{\mathbf{u}}(V) = q^m - q \cdot \text{wt}(\mathbf{u}) \neq 0$ for $\text{wt}(\mathbf{u}) \neq q^{m-1}$ (the Hamming weight of the vector $\mathbf{u}$ is denoted by $\text{wt}(\mathbf{u})$). $\square$

3 Necessary and sufficient conditions

We denote by $M_{q,n}$ the q -ary trivial MDS code (*maximum distance separable code*) with parameters $[n, n - 1, 2]_q$. Consider a code C of length $n = (q^m - 1)/(q - 1)$ over the field $\mathbb{F}_q$. Let a vector $(\mathbf{u}|\mathbf{v}) \in C$. We assume that $\mathbf{u}$ has length equal to $n - q^{m-1}$. For each vector $\mathbf{v} \in M_{q,q^{m-1}}$, we define the q -ary code $C'(\mathbf{v})$ of length $n - q^{m-1}$. Let

$$C'(\mathbf{v}) = \{\mathbf{u} \in \mathbb{F}_q^{n-q^{m-1}} \mid (\mathbf{u}|\mathbf{v}) \in C\}.$$

For each vector $\mathbf{u} \in \mathbb{F}_q^{n-q^{m-1}}$, we define the q -ary code $C''(\mathbf{u})$ of length q^{m-1} . Let

$$C''(\mathbf{u}) = \{\mathbf{v} \in M_{q,q^{m-1}} \mid (\mathbf{u}|\mathbf{v}) \in C\}.$$

Theorem 2. *For $q \neq 2$, the code C of length $n = (q^m - 1)/(q - 1)$ over the field $\mathbb{F}_q$ is a q -ary 1-perfect code of non-full-rank if and only if, when the code $C'(\mathbf{v})$ is a q -ary 1-perfect code of length $n - q^{m-1}$ for any $\mathbf{v} \in M_{q,q^{m-1}}$ and the code $C''(\mathbf{u}) \subset M_{q,q^{m-1}}$ is a q -ary code with parameters $(q^{m-1}, q^{q^{m-1}-m}, 3)_q$ for any $\mathbf{u} \in \mathbb{F}_q^{n-q^{m-1}}$.*

Proof. Let us prove the sufficiency of the conditions of the theorem. For this it is necessary to show that the number of code words in the code C is correct and the minimum distance $d(C)$ of the code C is 3. Let us show that the number of code words in the code C is correct. By the definition of the code C' , we have

$$|C| = \sum_{\mathbf{v} \in M_{q,q^{m-1}}} |C'(\mathbf{v})| = q^{q^{m-1}-1} q^{n-q^{m-1}-(m-1)} = q^{n-m}.$$

By the definition of the code C'' , we have

$$|C| = \sum_{\mathbf{u} \in \mathbb{F}_q^{n-q^{m-1}}} |C''(\mathbf{u})| = q^{n-q^{m-1}} q^{q^{m-1}-m} = q^{n-m}.$$

Now we show that the minimum distance $d(C) = 3$. Let the words $(\mathbf{u}|\mathbf{v})$ $(\mathbf{u}'|\mathbf{v}')$ belong to the code C . Assume that $\mathbf{u} = \mathbf{u}'$, then $\mathbf{v}, \mathbf{v}' \in C''$ and, therefore, $d((\mathbf{u}|\mathbf{v}), (\mathbf{u}'|\mathbf{v}')) \geq 3$. Assume that $\mathbf{v} = \mathbf{v}'$, then $\mathbf{u}, \mathbf{u}' \in C'$ and $d((\mathbf{u}|\mathbf{v}), (\mathbf{u}'|\mathbf{v}')) \geq 3$. Further assume that $\mathbf{u} \neq \mathbf{u}'$ $\mathbf{v} \neq \mathbf{v}'$, then $d(\mathbf{u}, \mathbf{u}') \geq 1$. Since $\mathbf{v}, \mathbf{v}' \in M_{q,q^{m-1}}$, then $d(\mathbf{v}, \mathbf{v}') \geq 2$ and, therefore, $d((\mathbf{u}|\mathbf{v}), (\mathbf{u}'|\mathbf{v}')) \geq 3$.

Consider the vector $\mathbf{w} \in \mathbb{F}_q^n$. Suppose that the first $n - q^{m-1}$ components of the vector $\mathbf{w}$ are equal to 0, and the remaining components of this vector are equal to 1. Then it is obvious that $\mathbf{w} \in \mathbf{C}^\perp$ and, therefore, the code C is a q -ary 1-perfect code of non-full-rank.

Next we prove the necessity of the conditions of the theorem. By the conditions of the theorem, the code C is a q -ary 1-perfect code of non-full rank and, consequently, there exists a nonzero vector $\mathbf{w} \in \mathbf{C}^\perp$. Then it follows from Theorem 1 that $wt(\mathbf{w}) = q^{m-1}$. Suppose that the first $n - q^{m-1}$ components of the vector $\mathbf{w}$ are equal to 0, and the remaining components of this vector are equal to 1. Consider the vector $(\mathbf{u}|\mathbf{v}) \in C$. Assume that $\mathbf{u}$ has a length equal to $n - q^{m-1}$. Then, since the first $n - q^{m-1}$ components of the vector $\mathbf{w}$ are equal to 0, then $\mathbf{v} \in M_{q,q^{m-1}}$.

Since $d(C) \geq 3$, then $d(C'(\mathbf{v})) \geq 3$. Since the length of the code $C'(\mathbf{v})$ is equal to $n - q^{m-1}$, it follows from the sphere-packing bound that $|C'(\mathbf{v})| \leq q^{n-q^{m-1}-(m-1)}$. Assume that $|C'(\mathbf{v}')| < q^{n-q^{m-1}-(m-1)}$ for some $\mathbf{v}'$. Then

$$|C| = \sum_{\mathbf{v} \in M_{q,q^{m-1}}} |C'(\mathbf{v})| = (q^{q^{m-1}-1} - 1)q^{n-q^{m-1}-(m-1)} + |C'(\mathbf{v}')| < q^{n-m},$$

which contradicts the condition of the theorem on the perfectness of the code C .

Since the code C is a q -ary 1-perfect code of length n and the length of the code $C''(\mathbf{u})$ is equal to q^{m-1} , it is known that $|C''(\mathbf{u})| \leq q^{q^{m-1}-m}$ see [8, 9]. Assume that $|C''(\mathbf{u}')| < q^{q^{m-1}-m}$ for some $\mathbf{u}'$. Then

$$|C| = \sum_{\mathbf{u} \in \mathbb{F}_q^{n-q^{m-1}}} |C''(\mathbf{u})| = (q^{n-q^{m-1}} - 1)q^{q^{m-1}-m} + |C''(\mathbf{u}')| < q^{n-m}.$$

□

For $q = 2$, the code $C''(\mathbf{u})$ has the parameters $(2^{m-1}, 2^{2^{m-1}-m}, 4)$, see [1].

From Theorem 2.1 of the paper [13] it follows, in particular, that for any q -ary 1-perfect code C of non-full rank and length $n = (q^m - 1)/(q - 1)$ there exists a monomial transformation ψ of the space $\mathbb{F}_q^n$ such that

$$\psi(C) = \{(\mathbf{u}|\mathbf{v}) \mid \mathbf{u} \in C'(\mathbf{v}), \mathbf{v} \in M_{q,q^{m-1}}\}, \quad (1)$$

where $C'(\mathbf{v})$ is a q -ary 1-perfect code of length $n - q^{m-1}$.

It follows from the Theorem 2 that any vector $\mathbf{w} \in C^\perp$ forms a representation of the code C in the form (1).

4 Concatenation construction

Let $q \neq 2$, m be any natural number not less than two, and $n = (q^m - 1)/(q - 1)$. Next, let $C_0^1, C_1^1, \dots, C_{(q-1)n}^1$ be a partition of the vector space $\mathbb{F}_q^n$ into q -ary 1-perfect codes of length n , and let $C_0^2, C_1^2, \dots, C_{(q-1)n}^2$ be a partition of q -ary trivial MDS code with parameters $[(q-1)n + 1, (q-1)n, 2]_q$ into q -ary codes with parameters $((q-1)n + 1, q^{(q-1)n-m}, 3)_q$ (such a partition exists by Theorem 2).

Theorem 3. *Given partitions $C_0^1, C_1^1, \dots, C_{(q-1)n}^1$, $C_0^2, C_1^2, \dots, C_{(q-1)n}^2$, and the permutation α acting on the index set $I = \{0, 1, \dots, (q-1)n\}$ determine the q -ary 1-perfect code*

$$C_\alpha = \{(\mathbf{u}|\mathbf{v}) \mid \mathbf{u} \in C_i^1, \mathbf{v} \in C_{\alpha(i)}^2\}$$

of length $qn + 1$.

Proof. We need to show that the number of code words in the code C_α is correct and the minimum distance $d(C_\alpha)$ of the code C_α is 3. Since a q -ary 1-perfect code of length n contains q^{n-m} codewords, then

$$|C_\alpha| = \sum_{\mathbf{v} \in M_{q,(q-1)n+1}} |C'(\mathbf{v})| = q^{(q-1)n} q^{n-m} = q^{qn+1-(m+1)}.$$

Next we show that the minimum distance $d(C_\alpha) = 3$. Let the words $(\mathbf{u}|\mathbf{v})$ $(\mathbf{u}'|\mathbf{v}')$ belong to the code C_α . Assume that $\mathbf{v} = \mathbf{v}'$, then $\mathbf{u}, \mathbf{u}' \in C_i^1$ for some $i \in I$ and, consequently, $d((\mathbf{u}|\mathbf{v}), (\mathbf{u}'|\mathbf{v}')) \geq 3$. Assume that $\mathbf{u} = \mathbf{u}'$, then $\mathbf{v}, \mathbf{v}' \in C_{\alpha(i)}^2$ and $d((\mathbf{u}|\mathbf{v}), (\mathbf{u}'|\mathbf{v}')) \geq 3$. Further assume that $\mathbf{u} \neq \mathbf{u}'$ $\mathbf{v} \neq \mathbf{v}'$, then $d(\mathbf{u}, \mathbf{u}') \geq 1$. Since $\mathbf{v}, \mathbf{v}' \in M_{q,(q-1)n+1}$, then $d(\mathbf{v}, \mathbf{v}') \geq 2$ and, therefore, $d((\mathbf{u}|\mathbf{v}), (\mathbf{u}'|\mathbf{v}')) \geq 3$. $\square$

By Theorem 2 (for the binary case, see. [1]) concatenation construction does not allow to construct full-rank codes, but allows constructing codes belonging to different switching classes [17]. (It is known that codes of full rank can be constructed using the method of switching for all $n = (q^s - 1)/(q - 1)$, where $s \geq 4$, see [1, 5, 15].) Etzion and Vardy [1] showed that by concatenation method all binary 1-perfect codes of non-full rank of length n can not be constructed. They proposed

the construction of binary 1-perfect codes, which is based on the so-called "*perfect segmentations*" and showed that their method allows obtaining codes different from binary 1-perfect codes constructed by the concatenation method. Heden [10] based on the partitioning of the space $\mathbb{F}_2^7$ into binary Hamming codes and partitions of the binary trivial MDS code of length 8 into binary extended Hamming codes using the concatenation construction constructed a binary 1-perfect code of length 15, which is not the code of Vasil'ev [3]. Solov'va [11] investigated the properties of binary 1-perfect codes, which are constructed by the concatenation method from partitions of the space $\mathbb{F}_2^n$ into Vasil'ev codes [3] and from the partition of MDS codes into extended Vasil'ev codes. There are many papers in which various partitions of the space $\mathbb{F}_q^n$ into 1-perfect codes are proposed (see, for example, [12]). Phelps [14] proposed a concatenation construction of binary extended 1-perfect codes of length $2n + 2$ starting from partitions of the binary trivial MDS code with parameters $[n + 1, n, 2]$ into binary extended 1-perfect codes of length $n + 1$. Phelps [18] enumerated all pairwise nonequivalent binary extended 1-perfect codes of length 16, which can be constructed by concatenation, and showed that this method allows to construct at least 963 such codes. As is known [20], there are 2165 pairwise nonequivalent binary extended 1-perfect codes of length 16. The number of pairwise nonequivalent binary extended 1-perfect codes of length 16 and rank 15 is equal to 175. Therefore, we can assume that by concatenation it is impossible to construct all binary extended 1-perfect codes of length 16, whose rank is less than 15. Phelps [19] generalized the binary concatenation construction that doubled the length of the code, and instead of permutations suggested using quasigroups; herewith the length of the code began to increase many times. Heden and Krotov [13] generalized the Phelps construction [19] to the q -ary case. The construction of Heden and Krotov is based on partitions of the space $\mathbb{F}_q^n$ into q -ary 1-perfect codes and codes with parameters $((q - 1)n + 1, q^{(q-1)n-m}, 3)_q$ are not used in it.

5 Ternary codes

The ternary Hamming code of length 13 has rank 10. The ternary nonlinear 1-perfect Lindström–Schönheim codes of length 13 have a rank equal to 11, see [6, 7]. In this section, using the concatenation method, we construct a ternary 1-perfect code of length 13 and rank 12.

Let the matrix

$$\begin{bmatrix} 0 & 0 & 0 & 0 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 0 & 1 & 1 & 1 & 0 & 0 & 0 & 1 & 1 & 1 & 2 & 2 & 2 \\ 1 & 0 & 1 & 2 & 0 & 1 & 2 & 0 & 1 & 2 & 0 & 1 & 2 \end{bmatrix}$$

be a parity-check matrix of the ternary Hamming code of length 13, which we denote by H . Consider the vector $0000111111111 \in H^\perp$. According to the theorem

2, this vector generates a ternary linear code C'' with parameters $[9, 6, 3]_3$, whose codewords belong to the ternary trivial MDS code $M_{3,9}$ with parameters $[9, 8, 2]_3$. Since the code C'' is linear and $C'' \subset M_{3,9}$, it generates a partition of $M_{3,9}$ into cosets. The number of cosets is 9. Let $m = 2$. Then the ternary Hamming code of length 4 forms a partition of the space $\mathbb{F}_3^4$ into cosets. The number of cosets is also 9. A ternary 1-perfect code of length 13 and rank 12, constructed using the concatenation construction, we denote by C_α . The permutation α is chosen in such a way that the code C_α contains the all-zero vector. It is obvious that for some permutation α the vectors

0	0	0	1	1	2	0	0	0	0	0	0	0
0	0	0	2	1	0	2	0	0	0	0	0	0
0	0	1	0	1	0	0	2	0	0	0	0	0
0	0	2	0	1	0	0	0	2	0	0	0	0
0	1	0	0	1	0	0	0	0	2	0	0	0
0	2	0	0	1	0	0	0	0	0	2	0	0
1	0	0	0	1	0	0	0	0	0	0	2	0
2	0	0	0	1	0	0	0	0	0	0	0	2
0	0	0	0	0	0	0	1	1	1	0	0	0
0	0	0	0	0	0	1	0	1	0	1	0	0
0	0	0	0	0	1	0	0	1	0	0	1	0
0	0	0	0	0	0	0	0	1	2	0	2	1

belong to the code C_α and are linearly independent.

The question of the existence of ternary 1-perfect codes of length 13 and rank 13 still remains open.

References

- [1] *Etzion T., Vardy A.* Perfect binary codes: Constructions, properties, and enumeration // IEEE Trans. Inf. Theory. 1994. V. 40, N 3. P. 754–763.
- [2] *Etzion T., Vardy A.* On perfect codes and tilings: problems and solutions // SIAM J. Discrete Math. 1998. V. 11, N 2. P. 205–223.
- [3] *Vasil'ev J. L.* On nongroup close-packed codes // Probl. Kibernet. 1962. V. 8. P. 375–378.
- [4] *Romanov A. M.* Hamiltonicity of minimum distance graphs of 1-perfect codes // Electron. J. Comb. 2012. Vol. 19, No. 1. P65.
- [5] *Romanov A. M.* On Full-Rank Perfect Codes over Finite Fields // Journal of Applied and Industrial Mathematics. 2016. V. 10, N. 3. P. 444–452.
- [6] *Schönheim J.* On linear and nonlinear single-error-correcting q -nary perfect codes // Inform. and Control. 1968. V. 12. P. 23–26.

- [7] *Lindström B.* On group and nongroup perfect codes in q symbols // Math. Scand. 1969. V. 25. P. 149–158.
- [8] *MacWilliams F. J., Sloane N. J. A.* The Theory of Error-Correcting Codes. Amsterdam: North-Holland Publishing Co., 1977.
- [9] *Delsarte P.* Bounds for unrestricted codes, by linear programming // Philips Research Reports. 1972. Vol. 27. P. 272289.
- [10] *Heden O.* A new construction of group and nongroup perfect codes // Inform. and Control. 1977. V. 34. P. 314–323.
- [11] *Solov'eva F. I.* On binary nongroup codes // Methody Diskr. Analiza 1981. V. 37. P. 65–76.
- [12] *Krotov D. S., Sotnikova E. V.* Embedding in q -ary 1-perfect codes and partitions // Discrete Mat. 2015. V. 338, N. 11. P. 1856–1859.
- [13] *Heden O., Krotov D. S.* On the structure of non-full-rank perfect q -ary codes. Advances in Mathematics of Communications. 2011. V. 5, N 2. P. 149–156.
- [14] *Phelps K. T.* A combinatorial construction of perfect codes // SIAM J. Algebraic Discrete Methods. 1983. V. 4. P. 398403.
- [15] *Phelps K. T., Villanueva M.* Ranks of q -ary 1-perfect codes // Designs, Codes and Cryptogr. 2002. V. 27, N 1-2 P. 139–144.
- [16] *Phelps K. T., Rifà J., Villanueva M.* Kernels and p -kernels of p^r -ary 1-perfect codes // Designs, Codes and Cryptogr. 2005. V. 37, N 2. P. 243–261.
- [17] *Phelps K. T., LeVan M. J.* Switching equivalence classes of perfect codes // Des. Codes Cryptogr. 1999. V. 16, N 2. P. 179–184.
- [18] *Phelps K. T.* An enumeration of 1-perfect binary codes // Australasian J. Combin. 2000. V. 21. P. 287–298.
- [19] *Phelps K. T.* A general product construction for error correcting codes // SIAM J. Algebraic Discrete Methods. 1984. V. 5, N 2. P. 224–228.
- [20] *Östergård P. R. J., Pottönen O., Phelps K. T.* The perfect binary one-error-correcting codes of length 15: Part II–Properties // IEEE Trans. Inform. Theory. 2010. V. 56, N. 6. P. 2571–2582.